2026 CAN-AM MAVERICK R MAX X RS

WITH SMART-SHOX

Triple Black



PACKAGE HIGHLIGHTS

- Smart-Shox™ Technology featuring Live Valve Gen 3
- 77 in. 4-link trailing arm with aluminum HD tall knuckle
- Smart-Lok^{™*} front differential
- FOX[†] 2.5 and FOX[†] 3.0 PODIUM RC2[†] Piggyback with bypass, dual speed compression and rebound adjustments
- 10.25 in. touchscreen display
- 32 in. ITP XNR Tenacity tyres
- 16 in. flow formed beadlock wheels
- · Front and rear cameras
- Telescopic steering wheel with infotainment controls
- Full hard roof
- Full heavy-duty HMWPE skid plate
- · Rear trailing arm rock guard
- 4-point harness with shoulder pads
- Premium high-performance LED headlights
- Can-Am LED signature lights
- · Center dashboard storage with cellphone holder
- X-package graphics/seats
- 1700 W magneto
- New skid plate and branch anti-intrusion
- 4 person seating capacity

| ENGINE | 999T DCT |
|----------------------|---|
| Туре | 240 hp, Rotax* 999T engine, 999 cc Turbocharged Triple-cylinder engine, liquid-cooled with integrated intercooler and high-performance air filter |
| Fuel Delivery System | Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI) |
| Transmission | Rotax® DCT, 7-speed with High & Extra Low range |
| Drive Train | Lockable front differential with exclusive Smart-Lok™* True 2WD / 4WD with front diff. lock / 4WD TRAIL ACTIV / 4WD TRAIL |
| Power Steering | High torque Gen 2 Tri-Mode DPS™ |
| SUSPENSIONS | |
| Front Suspension | Forged aluminum heavy-duty tall knuckle Double A-arm with sway bar 24 in. (61 cm) suspension travel |
| Front Shocks | FOX 2.5 PODIUM¹ Piggyback with bypass and Smart-Shox Technology featuring Live Valve Gen 3 (Dual Valve compression & rebound) |
| Rear Suspension | 4-link trailing arm with forged aluminum heavy-duty tall knuckle 24 in. (61 cm) suspension travel |
| Rear Shocks | FOX 3.0 PODIUM¹ Piggyback with bypass and Smart-Shox Technology featuring Live Valve Gen 3 (Dual Valve compression & rebound) |
| TYRES & WHEELS | |
| Front | XPS Trac Force 32 x 10 x 16 in. |
| Rear | XPS Trac Force 32 x 10 x 16 in. |
| Wheels | 16 in. aluminum flow formed beadlock |
| BRAKES | |
| Front | Dual 265mm disc brakes with 32mm hydraulic triple-piston calipers |
| Rear | Dual 255mm disc brakes with 32mm hydraulic twin-piston calipers |

DIMENSIONS & CAPACITIES

| 22 | | |
|----------------------|--|--|
| Estimated Dry Weight | 2,668 lb (1,214 kg) | |
| Chassis/Cage | High strength (dual phase) steel tubing and stampings | |
| LxWxH | 175 x 78.1 x 69.2 in. (444.5 x 198.4 x 175.8 cm) | |
| Wheelbase | 142.5 in. (362 cm) | |
| Ground Clearance | 17 in. (43.2 cm) | |
| Rack Capacity | 200 lb (90.7 kg) | |
| Storage Capacity | Total: 2.1 gal (7.9 L) | |
| Fuel Capacity | 13.2 gal (50 L) | |
| Person Capacity | 4 | |
| FEATURES | | |
| Gauge | 4.5 in. wide digital display with keypad & 10.25 in. touchscreen display | |
| 1 | 1100 4 (0 1 1 1 1 0 1 1 1 1 1 1 1 1 1 1 1 1 1 | |

| Gauge | 4.5 in. wide digital display with keypad & 10.25 in. touchscreen display |
|-------------------|---|
| Instrumentation | USB-A (2 charging ports & 1 communication port) DC outlet (10 A) |
| Anti-theft System | RF Digitally Encoded Security System (D.E.S.S.™) with Start/Stop button |
| Lighting | Premium high-performance LED headlights Can-Am LED signature lights |
| Winch | Winch-ready bumper (4,500 lb / 2,041.2 kg winch not installed) |
| Magneto | 1700 W |
| Protection | Full hard roof Premium half doors Front lower deflector Front / Rear anchor 3/8" full HD HMWPE skid plate Rock guard 4 point harnesses with shoulder pads |

WARRANTY

| Factory Warranty | 3-year unlimited km powertrain & Rotax® engine warranty |
|------------------|--|
| | and 1-year warranty & unlimited km on the rest of the unit |









