# **2026 CAN-AM MAVERICK R X RS**

## **WITH SMART-SHOX**



#### PACKAGE HIGHLIGHTS

- Smart-Shox™ Technology featuring Live Valve Gen 3
- 77 in. 4-link trailing arm with aluminum HD tall knuckle
- Smart-Lok™\* front differential
- FOX  $^{\dagger}$  2.5 and FOX  $^{\dagger}$  3.0 PODIUM RC2  $^{\dagger}$  Piggyback with bypass, dual speed compression and rebound adjustments
- · 10.25 in. touchscreen display
- 32 in. ITP XNR Tenacity tyres
- 16 in. flow formed beadlock wheels
- · Front and rear cameras
- Telescopic steering wheel with infotainment controls
- Full hard roof
- · Full heavy-duty HMWPE skid plate
- · 4-point harness with shoulder pads
- Premium high-performance LED headlights
- Can-Am LED signature lights
- · Center dashboard storage with cellphone holder
- X-package graphics/seats
- 1700 W magneto
- New skid plate and branch anti-intrusion
- 2 person seating capacity

ENGINE	999T DCT
Туре	240 hp, Rotax® 999T engine, 999 cc Turbocharged Triple-cylinder engine, liquid-cooled with integrated intercooler and high-performance air filter
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	Rotax® DCT, 7-speed with High & Low range
Drive Train	Lockable front differential with exclusive Smart-Lok™* True 2WD / 4WD with front diff. lock / 4WD TRAIL ACTIV / 4WD TRAIL
Power Steering	High torque Gen 2 Tri-Mode DPS™
SUSPENSIONS	
Front Suspension	Forged aluminum heavy-duty tall knuckle Double A-arm with sway bar 25 in. (63.5 cm) suspension travel
Front Shocks	FOX 2.5 PODIUM¹ Piggyback with bypass and Smart-Shox™ Technology featuring Live Valve Gen 3 (Dual Valve compression & rebound)
Rear Suspension	4-link trailing arm with forged aluminum heavy-duty tall knuckle 25.5 in. (64.8 cm) suspension travel
Rear Shocks	FOX 3.0 PODIUM¹ Piggyback with bypass and Smart-Shox Technology featuring Live Valve Gen 3 (Dual Valve compression & rebound)
TYRES & WHEELS	
Front	ITP XNR Tenacity 32 x 10 x 16 in.
Rear	ITP XNR Tenacity 32 x 10 x 16 in.
Wheels	16 in. aluminum flow formed beadlock
BRAKES	
Front	265mm disc brakes with 32mm hydraulic triple-piston calipers
Rear	255mm disc brakes with 30mm hydraulic twin-piston calipers

#### **DIMENSIONS & CAPACITIES**

Estimated Dry Weight	2,284 lb (1,036 kg)	
Chassis/Cage	High strength (dual phase) steel tubing and stampings	
LxWxH	140 x 78.1 x 71.5 in. (355.6 x 198.4 x 181.6 cm)	
Wheelbase	108 in. (274.3 cm)	
Ground Clearance	17 in. (43.2 cm)	
Rack Capacity	200 lb (90.7 kg)	
Storage Capacity	Total: 2.1 gal (7.9 L)	
Fuel Capacity	13.2 gal (50 L)	
Person Capacity	2	
FEATURES		
Gauge	4.5 in. wide digital display with keypad & 10.25 in. touchscreen display	

FEATURES	
Gauge	4.5 in. wide digital display with keypad & 10.25 in. touchscreen display
Instrumentation	USB-A (2 charging ports & 1 communication port) DC outlet (10 A)
Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start/Stop button
Lighting	Premium high-performance LED headlights Can-Am LED signature lights
Winch	Winch-ready bumper (4,500 lb / 2,041.2 kg winch not installed)
Magneto	1700 W
Protection	Full hard roof Premium half doors Front lower deflector Front / Rear anchor Full HMWPE skid plate 4 point harnesses with shoulder pads

### WARRANTY

Factory Warranty	3-year unlimited km powertrain & Rotax® engine warranty
	and 1-year warranty & unlimited km on the rest of the unit









